



### **Quality and performance for everyday mobility**

The **Action<sup>2</sup><sub>NG</sub>** provides essential support to positively enhance everyday mobility. It's easy handling makes the wheelchair ideal for basic needs with quality components to give effortless rolling performance both in doors and out. A great bonus to the **Action<sup>2</sup><sub>NG</sub>** is its cross compatibility throughout the **Action** range, offering familiarity and flexibility to a hugely successful **Action** family.



Trusted Solutions, Passionate People





**Features and Options**

**Light and comfortable**

With a weight from 14.9 kilos, the *Invacare Action<sup>2</sup><sub>NG</sub>* fulfills all essential functional requirements. The stable folding frame means the wheelchair is easy to handle, and being lightweight makes transportation trouble-free.

**Quality of life**

The tried-and-tested technology of the **Action** family products allow individuals to go wherever they desire. Cross-compatibility between a number of components on the **Action<sup>3</sup><sub>NG</sub>**, **Action<sup>4</sup><sub>NG</sub>** and **Action<sup>5</sup>** make this an ideal, basic, fleet product that can be easily adapted to meet individual needs. Also available in a transit version.



**Castor housing**

The castor housing is mounted outside to have more space for the feet when transferring of foot propelling.



**Adjustable center of gravity**

The rear wheel plate can be adjusted by 50 mm in depth and propose 3 positions in height.



**Anti-tippers**

Provide extra safety on slopes or uneven ground.

**Technical data**

<b>Self Propulsion</b>	380 / 405 / 430 / 455 / 480 mm	400 / 430 mm	460 / 485 / 510 mm	430 mm	200 - 280 mm (n°1) 230 / 255 mm (n°2)	330 / 460 mm
<b>Transit</b>	380 / 405 / 430 / 455 / 480 mm	400 / 430 mm	485 / 510 mm	430 mm	200 - 280 mm (n°1) 230 / 255 mm (n°2)	330 / 460 mm
<b>Self Propulsion</b>	80° / 0° - 80°	7° / 0° - 30°	SW + 200 mm	920 / 945 / 970 mm	1030 / 1080 mm	820 / 870 mm
<b>Transit</b>	80° / 0° - 80°	7° / 0° - 30°	SW + 145 mm	945 / 970 mm	950 mm	725 mm
<b>Self Propulsion</b>	325 mm	16.2 kg	8.9 kg	125 kg	Crash tested ISO 7176-19*	
<b>Transit</b>	240 mm	14.9 kg	12.1 kg	125 kg		

Invacare Limited  
 Pencoed Technology Park - Pencoed - Bridgend CF35 5AQ - United Kingdom  
 Tel: +44 1 656 776 222  
 Fax: +44 1656 776 220  
 E-mail: [uk@invacare.com](mailto:uk@invacare.com)  
 Sales Order E-mail: [ordersuk@invacare.com](mailto:ordersuk@invacare.com)  
[www.invacare.co.uk](http://www.invacare.co.uk)

Invacare Ireland Ltd  
 Unit 5 - Seatown Business Campus  
 Seatown Road - SWORDS - County Dublin - Ireland  
 Tel. +353 1 8107084  
 Fax +353 1 8107085  
 Email: [Ireland@invacare.com](mailto:Ireland@invacare.com)  
[www.invacare.ie](http://www.invacare.ie)

© 2016 Invacare International Sàrl  
 All rights reserved.

All information quoted is believed to be correct at time of print. Invacare reserves the right to alter product specifications without prior consultation.

Action2NG - UK - 01/2016 - 1526737




**Yes, you can.®**

**Frame colour**



Anthracite Black



Black nylon

Please note colors may vary slightly from those displayed above. These photographs are for general representation of product only.

**Upholstery**

All product dimensions are in millimetres to apply EN 12183 and EN 12184 standards.

\* Our wheelchairs comply above ISO standards and with ISO 10542, and have additional features providing increased levels of occupant security and safety whilst travelling in a motor vehicle. Wheelchair users should however transfer to the vehicle seat and use the vehicle installed restraint system whenever it is feasible.



Follow us on Twitter:  
[@Think\\_Mobility](https://twitter.com/Think_Mobility)



Follow us on YouTube:  
 Invacare Ltd - Think Mobility